

Hamilton Beach
COMMERCIAL

HBH650R Series Tempest[®] High-Performance Blender

No more
ice chunks



with Wave~Action[®] System

3 peak* HP motor powers through
ice and thick ingredients

Patented Wave~Action[®] system for
smooth results with no ice chunks

2 speeds, jump cycle, pulse and timer
for precision blending

Stackable 64 oz. / 1.8 L BPA-free
copolyester container

Extremely durable all-metal drive
coupling with jar pad sensor
to help extend coupling life

*input power



**HKR EQUIPMENT
CORPORATION**

FOODSERVICE EQUIPMENT, SERVICE, PARTS,
ACCESSORIES, & CONSUMABLES

9705 Kamagong St., San Antonio Village, Makati City

(632) 8897 1569 hkrequequipmentcorp.ph hkrequequipmentcorp
sales@hkr.com.ph hkr-equipmentcorporation www.hkr.com.ph

NSF[®]

For more Good Thinking[®] visit hamiltonbeachcommercial.com



Stackable 64 oz. / 1.8 L BPA-Free Copolyester Container

With laser-etched measurements that last a lifetime



Patented Wave~Action® System

Continually forces ingredients into the blades for a super-smooth drink profile

Timer with Auto Shutoff

Frees operators for other tasks

2 Speeds, Jump Cycle and Pulse

Offer precision blending for a wide variety of drinks

Powerful 3 Peak* HP Motor

Satisfies fast-paced blending demands

Sure Grip™ Feet

Prevent skidding



Sealed Lid Prevents Leaks

With easy-to-lift tab and filler cap



Jar Pad Sensor

Turns motor off when container is not in place to help prevent careless clutch grinding



Temperature Gauge

Alerts operator if motor overheats to prevent unnecessary burnout



*input power

HBH650R SERIES HIGH-PERFORMANCE BLENDER

SPECIFICATIONS:



Standard: Unit comes with base, one 64 oz. / 1.8 L container, and removable jar pad

Controls: Touchpad with high/ low, pulse, jump and timer

Motors: 3 peak* HP

Weight: 15 lbs / 6.8 kg (shipping)

Warranty: 3 years parts & labor. Lifetime warranty on blade and motor drive coupling.

HBH650R (120 V)

Electrical: 120 V, 60 Hz, 12.5 A
Cord Length: 75" / 1.9m



HBH650R-CE/-UK/-AU/-CCC (230 V)

Electrical: 220-240 V, 50-60 Hz, 1200 W
Cord Length: 1.9m / 75"



RoHS COMPLIANT