

Hamilton Beach
COMMERCIAL

HBH550R Series **FURY**TM High-Performance Blender

Powerful
precision
blending



with intuitive controls

3 peak* HP motor powers through
ice and thick ingredients

Patented Wave~Action® system delivers
super-smooth drink profile every time

Intuitive controls for precision blending:
paddle switches with 2 speeds
and pulse + timer

Stackable 64 oz. / 1.8 L BPA-free
copolyester container

Extremely durable all-metal drive
coupling with jar pad sensor
to help extend coupling life

*input power



**HKR EQUIPMENT
CORPORATION**

FOODSERVICE EQUIPMENT, SERVICE, PARTS,
ACCESSORIES, & CONSUMABLES

9705 Kamagong St., San Antonio Village, Makati City

☎ (632) 8897 1569

📧 hkrequipmentcorp.ph

📘 hkrequipmentcorp

✉ sales@hkr.com.ph

🌐 hkr-equipmentcorporation

🌐 www.hkr.com.ph

NSF[®]

For more Good Thinking[®] visit hamiltonbeachcommercial.com



**Stackable 64 oz. / 1.8 L
BPA-Free Copolyester Container**
With laser-etched measurements that last
a lifetime



Patented Wave~Action® System
Continually forces mixture into the blades
for a super-smooth drink profile

Timer with Automatic Shutoff
Frees operators for other tasks

Durable Paddle Switches
Built to last and easy to operate

Powerful 3 Peak* HP Motor
Powers through ice and thick
ingredients

Sure Grip™ Feet
Prevent skidding



Sealed Lid Prevents Leaks
With easy-to-lift tab and filler cap



**Extremely Durable All-Metal
Drive Coupling**
Built to withstand heavy use

Jar Pad Sensor
Turns motor off when container
is not in place to help prevent
careless clutch grinding



*input power

HBH550R SERIES HIGH-PERFORMANCE BLENDER

SPECIFICATIONS:



Standard: Unit comes with base, one 64 oz. / 1.8 L container, and removable jar pad

Controls: High/low, pulse paddle switches and timer

Motors: 3 peak* HP

Weight: 15.2 lbs / 6.9 kg (shipping)

Warranty: 3 years parts & labor. Lifetime warranty on blade and motor drive coupling.

HBH550R (120 V)

Electrical: 120 V, 60 Hz, 12.5 A
Cord Length: 75" / 1.9m



HBH550R-CE/-UK/-SA/-CCC (230 V)

Electrical: 220-240 V, 50-60 Hz, 1200 W
Cord Length: 1.9m / 75"



RoHS COMPLIANT

