

MF 30.2 PLUS

REACH IN Blast Chiller and Shock Freezer



MultiFresh®: the multi-function assistant that will organize your production and processes with flexibility 24 hours a day. MultiFresh is the first and only machine in the world that can run operating cycles with temperatures from 185°F to -40°F preserving its consistency, moisture content, and nutritional properties. Multifunction 7" touchscreen display, product specific cycles, wide range of options, customization of all the parameters for each cycle.

Capacity

(18"x13") sheet pans (5)

(12"x20") sheet pans (6)

Yield

Blast chilling capacity (194/+37°F) 66 Lbs

Shock freezing capacity (194/-0°F) 66 Lbs

Product Warranty Protection

- 2 years from date of installation, after sending the installation report, on the parts (see warranty condition)

Certification



Standard Construction Features

- (2) stainless steel wire shelves
- All type 304 stainless steel construction
- CFC-free high-density polyurethane insulation
- Full width door with low-temperature resistant magnetic gasket
- Irinox Patented die-stamped interior door liner to magnetically store core temperature probe
- MultiSensor® 5-point probe for perfect temperature control.
- Automatic switch from manual mode (timed) to automatic mode (with probe) when probe is not inserted
- Removable stainless steel pan supports, adjustable spacing
- Approved 404a refrigerant used in sealed system
- High efficiency evaporators with multiple injection points
- Data port & Wi-Fi capable data transfer to HACCP software
- Door hinged left (standard)
- 4" stainless steel adjustable legs
- End-of-cycle hold mode
- Self-contained, air-cooled energy efficient condensing unit
- Manual defrosting required at the end of the day
- SANIGEN sanitation system

Unique Design and Performance Features

- Available heat cycles: THAWING, HOLDING (hot or cold), REGENERATION, PASTEURIZATION, PROOFING, LOW TEMPERATURE COOKING
- Indirect air distribution and special airflow pattern to ensure perfect temperature uniformity
- Adjustable MULTIRACK® tray holder, which allows operators to double the quantity of trays loaded in each model
- MultiFresh® touch screen
- Easily accessible evaporators, waterproof fans and removable magnetic condenser filter
- Core probe magnetically secured to door when not in use

Option and Accessories

- Door hinged Right
- 4 Casters (2 with locks)
- Sous-vide core probe
- Additional core probe
- Additional wire shelves
- Cityline Water Condensation unit
- Remote Condensation unit


HKR EQUIPMENT CORPORATION

FOODSERVICE EQUIPMENT, SERVICE, PARTS,
ACCESSORIES, & CONSUMABLES

9705 Kamagong St., San Antonio Village, Makati City

(632) 8897 1569 hkrequipmentcorp.ph hkrequipmentcorp.com
sales@hkr.com.ph hkr-equipmentcorporation.com www.hkr.com.ph

Cabinet



★ Main power cable

▲ Drain pipe Ø 31

	Cabinet
Width	34 1/4"
Depth	35 1/2"
Height w/legs not extended	37"
Height w/casters	35"
Weight	309 Lbs

Electric Data / Power Requirements	
Electric Supply	208V 60 Hz 2 Phase
Full load amps	11,70 A
Total Rating (FLI)	2,30 kW
Main power cable	AWG 3G15

Key Refrigeration System Data	
Compressor Rating (HP)	1,0
Refrigeration Yield (14/104 °F) btu/h	10724
Condensing Rating (14/104 °F) btu/h	15686
Refrigeration Type	R404
Maximum Ambient Air Temperature	90 °F

INSTALLATION NOTES

Compressor requires 4" minimum rear wall clearance or 3" right and left clearance

Continued product development may require specification changes without prior notice.

Irinnox North America

9990 NW 14th Street Suite 107 Miami FL 33172

Phone. (786) 870 5064 Fax. (786) 391 2467

www.irinnoxprofessional.com/usa/ | info@irinnoxnorthamerica.com